KD42

Dijital Tartım İndikatörü | Digital Weighing Indicator

Ürün Veri Sayfası
Product Data Sheet



TR

KD42 Dijital Tartım İndikatörü, CE, OIML R60 ve EU tip onay sertifikalarına sahiptir. Paslanmaz çelik kasası ve membran tip switch buton tuş takımı ile endüstriyel kullanıma uygundur. Tır ve kamyon kantarları için geliştirilmiş yazılımı ile harici bilgisayar ve kantar programına ihtiyaç duymaz. 16 adete kadar Kobastar dijital Load Cell kullanımını destekler. Otomatik ve manuel ayar yapmaya imkan verir. Hata durumunda uyarı verir.

EN

KD42 Digital Weighing Indicator holds CE, OIML R60, and EU type approval certificates. Featuring a stainless steel casing and membrane switch keypad, it's ideal for industrial use. Its specialized software eliminates the need for external computer or scale software for truck and vehicle scales. Supporting up to 16 Kobastar digital Load Cells, it offers both automatic and manual adjustments and error alerts.

Teknik Özellikler | Technical Features

Doğruluk Sınıfı	1/30000
AB Tip Onay	(III) n=3000 Division
Ekran	20mm Kırmızı LED
Yük Hücresi Arayüzü	Rs485 Mode, Max. gönderme mesafesi 75m.
Gönderim Hızı	19200bps
Yük Hücresi Besleme	DC12V / 750mA
Yük Hücresi Sayısı	1 - 16 Adet (Kobastar Dijital Yük Hücresi)
Harici Ekran Bağlantısı	20mA Current Loop, 600bps, 100m.
Yazıcı Arayüzü	Parallel Yazıcı Çıkışı (Epson, Panasonic Etc.)
Seri Portlar	Rs232 / Rs485
Kalibrasyon	Doğrusallık ayarlama fonksiyonu
Filtreleme	Dijital vibrasyon filtreleme
RTC	Gerçek Zamanlı Tarih ve Saat
Enerji Kaynağı	AC110~220V - 50hz / DC12V/7Ah Şarj olabilen batarya
Çalışma Sıcaklığı	-10 ~ 40°C
Ölçüler	339x110x230
Ağırlık	3,6Kg

Accuracy Class	1/30000
EU Type Approval	(III) n=3000 Division
Display	20mm Red LED
Load Cell İnterface	Rs485 Mode, Max. transmission distance 75m.
Transmission Speed	19200bps
Load Cell Supply	DC12V / 750mA
Number of Load Cells	1 - 16 Units (Kobastar Digital Load Cell)
EDC	20mA Current Loop, 600bps, 100m.
Printer İnterface	Parallel Printer Output (Epson, Panasonic, etc.)
Serial Ports	Rs232 / Rs485
Calibration	Linearity Adjustment Function
Filtering	Digital Vibration Filtering
Real-Time Clock (RTC)	Real-Time Date and Time
Power Supply	AC110~220V - 50hz / DC12V/7Ah Rechargeable Battery
Operating Temp.	-10 ~ 40°C
Dimensions	339x110x230
Weight	3.6Kg

Uygulama Alanı | Application

Paltform basküller / Tank ve silo tartım
Platform scales / Tank and silo weighing