BM8G

FEATURES

- Stainless steel IP68 shear beam load cell
- Hermetically sealed
- Robust and wide mounting surface
- Suitable for harsh enviroN.ment
- Current calibrated (sc-option)



AVAILABLE MODELS


xxkg	C3/C4	BM8G-xx-xxkg-5B
xxt	C3/C4	BM8G-xx-xxt-5B
xxklb	C3	BM8G-C3-xxK-5B
500kg-10t approved by OIML C3; 500kg-2t approved by OIML C4.		

test certificate no. D09-07.22
C of C no R60/2000-DE1-10.07

SPECIFICATION


Accuracy class		OIML R60 C3		OIML R60 C4
Output sensitivity (=FS)	mV/V	2.0 ± 0.002		
Maximum capacity (E_{max})	t	0.5/1/2/5/7.5/10		
	lb	1K/2K/5K/10K/15K		
Maximum number of load cell intervals (nLC)		3000		4000
Ratio of minimum LC verification interval $Y=E_{max} / V_{min}$		10000		15000
Combined error	%FS	± 0.0230		± 0.0175
Minimum dead load	%FS	0		
Safe overload	%FS	150		
Ultimate overload	%FS	300		
Zero balance	%FS	± 1.0		
Excitation, recommended voltage	V	5 ~ 15 (DC)		
Excitation maximum	V	18 (DC)		
Input resistance	Ω	350 ± 3.5		
Output resistance	Ω	350 ± 3.5		
Insulation resistance	MΩ	⩾ 5000 (50VDC)		
Compensated temperature	℃	-10 ~+40		
Operating temperature	℃	-35 ~ +65		
Storage temperature	℃	-40 ~ +70		
Element material		Stainless steel		
Recommended torque on fixation	N.m	M12: 100	M20:450	M24:750
Ingress protection (according to EN 60529)		IP68		

OUTLINE DIMENSION MM(INCH)



Capacity \ Dimension (mm)	A	B	C	D	E	L	L1	L2	L3	H	h	h1	I
0.5t-2t (1klb-5klb)	17.48(0.69)	30.3(1.19)	13.9(0.55)	36.5(1.44)	101.6(4.00)	203.2(8.00)	19.05(0.75)	63.5(2.50)	98.43(3.88)	47.63(1.88)	36.5(1.44)	11.8(0.46)	17(0.67)
1t, 2t, 2klb, 5klb	/	/	/	/	/	/	/	/	/	/	/	11.9(0.47)	/
5t,7.5t-W2 (10K1b-15K1b)	25.5(1.00)	41.4(1.63)	22.23(0.88)	47.36(1.86)	117.5(4.63)	234.95(9.25)	20.62(0.81)	66.7(2.63)	123.8(4.87)	69.85(2.75)	47.64(1.88)	15.75(0.62)	17(0.67)
5t-W1	25.5(1.00)	41.3(1.63)	22(0.87)	47.5(1.87)	111(4.37)	234.95(9.25)	20.62(0.81)	66.7(2.63)	123.8(4.87)	50(1.97)	47.6(1.87)	15.8(0.62)	17(0.67)
5t-W2	25.5(1.00)	41.4(1.63)	22.23(0.88)	47.37(1.86)	117.5(4.63)	234.95(9.25)	20.62(0.81)	66.7(2.63)	123.8(4.87)	69.85(2.75)	47.6(1.87)	15.75(0.62)	17(0.67)
10t	25.5(1.00)	41.4(1.63)	25(0.98)	55(2.17)	111(4.37)	234.95(9.25)	20.62(0.81)	66.7(2.63)	123.8(4.87)	69.85(2.75)	58.6(2.31)	15.75(0.62)	17(0.67)

WIRING



- Adopt shielded, 4 conductor cable: Φ5mm
- Standard cable length: 5m